

“The Best Hose Suspension in the World”



MODEL  
**HB 200 ED**

For  
**Hose I.D. 2” (5 cm)**



Material:	<b>URETHANE</b>	
Length:	<b>18" / 45.7 cm</b>	
Shipping Weight:	<b>4.5 lbs / 2 kgs</b>	
Shipping Dimensions:	<b>21 x 8 x 4" / 53 x 21 x 10 cm</b>	
Sling Model:	<b>Metal "D-Ring" Sling</b>	
Sling Type:	<b>RS 16D</b>	
*Sling height:	<b>7.25" / 18.4 cm</b>	
Sling Material:	<b>UV Resistant Treated Polyester</b>	
Rated Capacity:	<b>1350 lbs/ 612 kgs @ 5:1 WLL</b>	<b>437 kgs/ 964 lbs @ 7:1 WLL</b>
Maximum Temperature:	<b>200° F / 93.3° C</b>	

\*Measured from top of the bun to the top of the sling

**Notes:** Also available with Type 4 Hook-Eye sling (Model # RS 234H) for heavy duty jobs.

(WLL for RS 234H: 2000lb / 907kgs @ 5:1 or 648kgs / 1428lbs @ 7:1)

**CE certified slings available at a rated capacity of 500 kgs @ 7:1**



© 2015 property of IceCap Equity Corp. All Rights Reserved.

*USA & Canada (Toll Free)*

Tel: 888-829-3773

Fax: 877-382-9626

*International*

Tel: 403-294-0275

Fax: 403-294-0274

Email: [info@hosebun.com](mailto:info@hosebun.com)