

“The Best Hose Suspension in the World”



MODEL  
**HB 200 SRD**  
For  
**Hose I.D. 2" (5 cm)**



|                      |  |                                       |
|----------------------|--|---------------------------------------|
| Material:            | <b>URETHANE</b>                        |                                       |
| Length:              | <b>12" / 30.5 cm</b>                   |                                       |
| Shipping Weight:     | <b>2.5 lbs / 1.1 kgs</b>               |                                       |
| Shipping Dimensions: | <b>13 x 5 x 3.5" / 33 x 13 x 9 cm</b>  |                                       |
| Sling Model:         | <b>Metal "D-Ring" Sling</b>            |                                       |
| Sling Type:          | <b>RS 16D</b>                          |                                       |
| *Sling height:       | <b>7.25" / 18.4 cm</b>                 |                                       |
| Sling Material:      | <b>UV Resistant Treated Polyester</b>  |                                       |
| Rated Capacity:      | <b>1350 lbs/ 612 kgs<br/>@ 5:1 WLL</b> | <b>437 kgs/ 964 lbs<br/>@ 7:1 WLL</b> |
| Maximum Temperature: | <b>200° F / 93.3° C</b>                |                                       |

\*Measured from top of the bun to the top of the sling

**Notes:** Also available with Type 4 Hook-Eye sling (Model # RS 234H) for heavy duty jobs.

(WLL for RS 234H: 2000lb / 907kgs @ 5:1 or 648kgs / 1428lbs @ 7:1)

**CE certified slings available at a rated capacity of 500 kgs @ 7:1**



© 2015 property of IceCap Equity Corp. All Rights Reserved.

*USA & Canada (Toll Free)*

Tel: 888-829-3773

Fax: 877-382-9626

*International*

Tel: 403-294-0275

Fax: 403-294-0274

Email: [info@hosebun.com](mailto:info@hosebun.com)